



Model KII

Features:

- Super strong heat treated load chain (GR1000)
- Hooks of easier handling shape (i.e. opening of hooks wider for easier handling)
- Tough gear case reinforced with four ribs and four knock pins
- Rolled edge hand wheel cover (allows for smooth operation when pulled at a slant)
- Strong anti corrosive electrostatic powder coating
- Wet friction discs for longer life
- Unique chain guide
- Anchor plate to avoid over lifting / lowering
- Very light and compact (11.4kg / 1 tonne)
- Designed to JIS B8802/12 design standard
- Manufactured to ISO 9001 QAS
- Rated best chain block worldwide
- Fitted standard with double ratchet pawl
- Also available with overload protection device



Product Code	Model Nr	Working Load Limits (Tonne)	Standard Lift (m)	Manufacturer's Test Load (Tonne)	Head Room (mm)	Hand Effort to Lift Full Working Load (kgf)	Load Chain no. of Falls	Net Mass (kg)
A00200013	KII - 0.5	0.5	3	150% x max. working load	275	27	1	9
A00200014	KII - 1	1	3		300	31.5	1	11.4
A00200015	KII - 1.6	1.6	3		335	41.5	1	14.7
A00200016	KII - 2	2	3		375	40	1	21
A00200021	KII - 3S	3	3	125% x max. working load	410	40.5	1	25.4
A00200018	KII - 3.1	3.1	3		530	47.5	2	24
A00200019	KII - 5	5	3		625	48	2	39.5
A00200020	KII - 10	10	3		775	52.5	4	82

Dimensions:

WLL (Tonne)	A	B	C	D	E	F
KII-0.5	140	155	58	33	26	36
KII-1	160	160	62	35	30	43
KII-1.6	183	167.5	65	37	35	48
KII-2	215	183	66	41	38	53
KII-3S	233	190	70	44	40	55
KII-3.1	230	167.5	110	62.5	44	60
KII-5	282	190	166	78.5	53	70
KII-10	358	190	300	98	70	85

