



18x7 = 6x(1+6)+12x(1+6)IWRC (Non Rotating)

Features:

- Suitable for longlift cranes, tower cranes, mobile cranes + dockside cranes
- Only available in ungalvanised with light lubrication - A1
- All manufactured to EN 12385
- Supplied with manufacturers' certificate of conformance

Rope Diameter (mm)	Unit Weight kg/m	Wire Tensile	
		1770 N/mm ²	1960 N/mm ²
		Minimum Breaking Load (MBL) kN	
6.00	0.121	22.26	24.17
7.00	0.218	29.86	32.42
8.00	0.281	38.82	42.14
9.00	0.347	48.14	52.26
9.50	0.398	55.40	60.15
10.00	0.401	58.10	64.30
11.00	0.485	70.20	77.80
11.50	0.562	78.89	85.65
12.00	0.577	83.60	92.60
13.00	0.678	98.10	108.6
14.00	0.786	113.8	126
15.00	0.902	131	145
16.00	1.027	149	165
18.00	1.299	188	208
19.00	1.448	210	232
20.00	1.604	232	257
22.00	1.941	281	311
24.00	2.310	334	370
25.00	2.506	363	402
26.00	2.711	392	435
28.00	3.144	455	504
29.00	3.372	488	541
32.00	4.106	594	658