



Single Sheave



Double Sheave



Treble Sheave

Features:

- Available in capacities of up to 40 000 kg
- Grease nipples for positive greasing
- Test certificates supplied
- Blank and drilled sheave wheels any size available
- Suitable for steel wire ropes
- Fitted with phosphor bronze bushed sheaves
- Available with hook and safety latch

Single Sheave Blocks with Swivel Oval Eye and Becket

Product Code	W.L.L	Rope Dia	A	B	C	D	E	F	G
	*(tonne)	mm	mm	mm	mm	mm	mm	mm	mm
K20250025	0.5	10-13	110	40	300	100	25	60	30
K20250028	1.0	10-13	135	50	390	125	25	60	35
K20250031	2.0	10-13	165	70	460	150	32	60	35
K20250034	3.0	13-16	210	80	570	200	40	70	32
K20250037	5.0	16-20	265	90	700	250	45	75	35
K20250040	7.5	16-20	320	100	800	300	55	80	40
K20250043	10.0	20-22	370	120	900	350	60	110	65

Double Sheave Blocks with Swivel Oval Eye and Becket

Product Code	W.L.L	Rope Dia	A	B	C	D	E	F	G
	*(tonne)	mm	mm	mm	mm	mm	mm	mm	mm
K20250026	0.5	10-13	110	66	300	100	25	60	30
K20250029	1.0	10-13	135	91	390	125	25	60	30
K20250032	2.0	10-13	165	111	460	150	32	60	35
K20250035	3.0	13-16	210	126	570	200	40	70	32
K20250038	5.0	16-20	265	141	700	250	45	75	35
K20250041	7.0	16-20	320	151	800	300	55	80	40
K20250044	10.0	20-22	370	176	900	350	60	110	65

Treble Sheave Blocks with Swivel Oval Eye and Becket

Product Code	W.L.L	Rope Dia	A	B	C	D	E	F	G
	*(tonne)	mm	mm	mm	mm	mm	mm	mm	mm
K20250027	0.5	10-13	110	99	300	100	25	60	30
K20250030	1.0	10-13	135	132	390	125	25	60	30
K20250033	2.0	10-13	165	152	460	150	32	60	35
K20250036	3.0	13-16	210	172	570	200	40	70	32
K20250039	5.0	16-20	265	192	700	250	45	75	35
K20250042	7.0	16-20	320	202	800	300	55	80	40
K20250045	10.0	20-22	370	232	900	350	60	110	65

