

- Material: Mild steel
  - Safety factor: MBL equals 5 x WLL
  - Finish: Hot dipped galvanized
  - Note: End fittings of 6 and 8mm rigging screws are electro-galvanized
- The following types are available: jaw/jaw - eye/eye - jaw/eye

**Clevis / Clevis**



a	b	Total Closed c	Length Open d	e	f	g	h	i	j	k	Work Load Limit	Approx Mass per pce
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	tonne	kg
6	100	170	248	5	19	7	20	13	11	11	0.20	0.14
8	108	189	273	6	225	9	24	14	12	12	0.32	0.24
10	125	216	306	8	26	10.5	28	19	13	13	0.5	0.53
12	195	232	478	10	32	13	34	22	30	15	0.7	0.83
16	230	284	569	12	39	18	42	28	40	20	1.2	1.49
20	270	455	665	16	46	20	51	33	50	24	1.5	2.54
22	286	493	723	20	55	25	55	38	50	24	2.2	3.34
24	325	552	802	22	32	70	70	46	56	28	3.2	4.65
33	370	673	936	30	85	38	82	60	70	35	4.8	10.5
39	400	712	1018	33	86	45	85	76	80	40	6	12.8
45	400	760	1050	39	105	50	100	86	90	45	8.5	20.8
48	400	820	1110	45	120	58	118	92	100	45	11	24

- Material: Mild steel
  - Safety factor: MBL equals 5 x WLL
  - Finish: Hot dipped galvanized
  - Note: End fittings of 6 and 8mm rigging screws are electro-galvanized
- The following types are available: jaw/jaw - eye/eye - jaw/eye

**Clevis / Eye**



A	B	Total Closed C	Length Open D	E	F	G	Work Load Limit	Approx Mass per pce
mm	mm	mm	mm	mm	mm	mm	tonne	kg
6	100	165	245	5.5	11	11	0.2	0.13
8	108	178	261	6	12	12	0.32	0.2
10	125	210	308	8.5	13	13	0.5	0.6
12	195	325	484	11	30	15	0.7	0.8
16	230	380	564	12	40	20	1.2	1.4
20	270	455	673	16	50	24	1.5	2.4
22	295	495	736	16	50	24	2.2	3
24	325	545	806	19	56	28	3.2	3
33	370	665	961	29	70	35	4.8	9
39	400	725	1032	34	80	40	6	11.5
45	400	760	1050	30	90	45	8.5	20.8
48	400	820	1110	35	100	45	11	24

