

Tusker® Thrust Bearing Swivels



- Material: Carbon steel
- Safety factor: 5 times WLL = minimum breaking strength
- Finish: Yellow painted
- Swivels for all safe working loads are available in any of the configurations illustrated.
- Swivels have been individually proof tested.



| Type | Working Load Limit | Total Length | Thickness Eye | Outside Dia | Outside Jaw Width | Inside Jaw Width | Hole in Jaw | Hole in Eye | Approx Mass per pce |
|------|--------------------|--------------|---------------|-------------|-------------------|------------------|-------------|-------------|---------------------|
| | tonne | mm | mm | mm | mm | mm | mm | mm | kg |
| | | A | B | C | D | E | F | G | |
| H-J | 3 | 273 | - | 75 | 41 | 20 | 20 | - | 5 |
| E-J | 3 | 203 | 20 | 75 | 41 | 20 | 20 | 23 | 4 |
| J-J | 3 | 210 | - | 75 | 41 | 20 | 20 | - | 4.5 |
| H-E | 3 | 270 | 20 | 75 | - | - | - | 23 | 4.5 |
| J-E | 3 | 203 | 20 | 75 | 41 | 20 | 20 | 23 | 4 |
| E-E | 3 | 200 | 20 | 75 | - | - | - | 23 | 3.6 |
| H-J | 5 | 337 | - | 95 | 57 | 25 | 23 | - | 9.5 |
| E-J | 5 | 244 | 25 | 95 | 57 | 25 | 23 | 32 | 7.7 |
| J-J | 5 | 251 | - | 95 | 57 | 25 | 23 | - | 8.2 |
| H-E | 5 | 330 | 25 | 95 | - | - | - | 32 | 9 |
| J-E | 5 | 244 | 25 | 95 | 57 | 25 | 23 | 32 | 7.7 |
| E-E | 5 | 238 | 25 | 95 | - | - | - | 32 | 6.8 |
| H-J | 7.5 | 457 | - | 121 | 70 | 35 | 29 | - | 20.8 |
| E-J | 7.5 | 318 | 32 | 121 | 70 | 35 | 29 | 35 | 16 |
| J-J | 7.5 | 330 | - | 121 | 70 | 35 | 29 | - | 16.3 |
| H-E | 7.5 | 448 | 32 | 121 | - | - | - | 35 | 20.4 |
| J-E | 7.5 | 321 | 32 | 121 | 70 | 35 | 29 | 35 | 16 |
| E-E | 7.5 | 308 | 32 | 121 | - | - | - | 35 | 15 |
| H-J | 10 | 479 | - | 121 | 75 | 44 | 38 | - | 24 |
| E-J | 10 | 362 | 44 | 121 | 75 | 44 | 38 | 41 | 18.6 |
| J-J | 10 | 378 | - | 121 | 75 | 44 | 38 | - | 18.6 |
| H-E | 10 | 470 | 44 | 121 | - | - | - | 41 | 24 |
| J-E | 10 | 368 | 44 | 121 | 75 | 44 | 38 | 41 | 19 |
| E-E | 10 | 352 | 44 | 121 | - | - | - | 41 | 18 |
| H-J | 15 | 578 | - | 140 | 89 | 44 | 38 | - | 36 |
| E-J | 15 | 429 | 51 | 140 | 89 | 44 | 38 | 51 | 30 |
| J-J | 15 | 448 | - | 140 | 89 | 44 | 38 | - | 29 |
| H-E | 15 | 568 | 51 | 140 | - | - | - | 51 | 35 |
| J-E | 15 | 438 | 51 | 140 | 89 | 44 | 38 | 51 | 30 |
| E-E | 15 | 419 | 51 | 140 | - | - | - | 51 | 28 |

