



Equipped with
**OVERLOAD
LIMITER**



*Improved safety
and durability*

KITO LEVER HOIST

Model **L5**
0.8t~9t



*Easy Operation with
a compact, low
headroom design.*

The lever slips! Prevents the hoist from excessive overload lifting.

In the event of excessive overload lifting, the overload limiter is activated and the lever slips. It is a device to improve operator's safety and hoist's durability.




KITO
LEVER HOIST
CE WLL 1.6t
34kg=1.6t
Equipped with
**OVERLOAD
LIMITER**

KITO LEVER HOIST Model L5 0.8t~9t

7 standard capacities with wide range from 0.8t to 9t. Choose the one that best suits your application.

Equipped with
**OVERLOAD
LIMITER**




KITO model L5 lever hoist performs in the most demanding applications. Low headroom, lightweight, compact design. Developed for professional purposes putting emphasis on operator safety and durability. The overload limiter prevents the hoist from excessive overload lifting. It can be used in various fields including freight industry, bridgework industry, forest industry, woodworking industry, shipbuilding industry, construction industry, and so forth.



Specifications and Dimensions

Rated load (W.L.L.) (t)	0.8	1	1.6	2.5	3.2	6.3	9
Code	LB008	LB010	LB016	LB025	LB032	LB063	LB090
Standard lift (m)	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Hand-pull to lift full load (N) [kg]	284 [29]	353 [36]	333 *2 [34]	363 *2 [37]	363 *2 [37]	372 *2 [38]	382 *2 [39]
Load chain diameter x chain fall (mm)	5.6x1	5.6x1	7.1x1	8.8x1	10x1	10x2	10x3
Test load (kg)	1200	1500	2400	3800	4800	7900	11300
Mass (Net weight) *1 (kg)	6	6.2	8.4	11.6	15.2	26.2	40.2
Shipping weight (Approx.) (kg)	6.3	6.5	8.7	12	16.2	27.2	42.2
Weight for additional one meter of lift (kg)	0.7	0.7	1.1	1.7	2.3	4.7	7
Dimensions (mm)	a	144	144	159	173	190	190
	b	119	119	126	150	159	217
	C	280	300	335	375	395	540
	D	245	245	265	265	415	415
	e	97	97	100	102	112	112
	g	23.5	29	32	36.5	39	50
	s	35.5	42.5	42.5	47	50	60
	t	14	15	19	21	24.5	34



*1.5m lift standard, non-standard lift also available. Additional chain cannot be added to original length of purchased chain as KITO chains are heat treated.

When ordering, specify the length of chain in advance or consult your local Kito distributor.

*Lever hoist with Kito Load signal (overload detection unit) are also available.

*1 :The mass(Net weight) is for the standard load-lifting height.

*2 :Does not accord with EN13157

Features and performances of all the products described in this catalogue are designed for their own intended purposes.

KITO will not be held liable for any malfunction, lack of performance or accident if the product is being used in conjunction with any other equipment.

If the product is to be used for unintended purposes, please confirm with your dealer in advance.

All specifications herein are subject to change without notice.

Distributed by:



KITO CORP.



Tokyo Opera City Tower 16th Floor,
3-20-2 Nishi-Shinjuku, Shinjuku-ku, Tokyo 163-1416, JAPAN

TEL: +81-3-5371-7315, +81-3-5371-7341

FAX: +81-3-5371-7349

E-mail: overseas@kito.co.jp

URL: <http://www.kito.co.jp>

